

Hermitage Collection Datasheet

Product Description: Premium engineered hardwood flooring

Warranty: Residential use for 25 years, and 5 years for normal indoor light commercial use

from the date of purchase.

Certification: Conformité Européenne (CE Marking)

FloorScore Certification

California Air Resources Board (CARB): calCOMPlaint™ Phase 2

Size & Spec

Dimension	7-1/2 in. x 6-1/3 ft. random length		
	9 in. x 7 ft. random length		
Thickness	5/8 in. (6mm wear layer)		
Construction	2 layers engineered hardwood		
Edges & Ends	Micro bevel		
Color Treatment	Smoked / Stained		
Wear Finish	UV-cured urethane		
Grade	Rustic		
	Select & Better		
Packing	Width 7-1/2 in.: 19.43 sq. ft./ box, 60 boxes/ pallet		
	Width 9 in.: 26 sq. ft./ box, 45 boxes/ pallet		

Test Data

Thickness swelling rate due to	CNS 11342	3%
water absorption test (%)		
Formaldehyde Emission Test	CARB ATCM	Less than 0.05 ppm
Fire Retardant	CNS 7614	Ignition Time: 30 sec.
	(A method)	After-flame time: 4.4 sec.
		After-glow time: 4.4 sec.
		Char distance: 5.9 cm
Contamination resistance	CNS 8058	No change on surface
	(B method)	
Impact Resistance	CNS 2215	No chaps, cracks, stripping and penetrate;
(W2-500, 100 cm)		diameter of depression: 11.2mm
Bending, sticking up, distortion test	CNS 11342	Stick up 0.4mm without using disorder